

### REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 18 in the underlying PCT Application No. PCT/DE03/03213 and adds new claims 19 to 38. The new claims, *inter alia*, conform the claims to United States Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.121(b)(3), the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121(b)(3)(iii) and § 1.125(b)(2), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) is respectfully requested.

The underlying PCT Application No. PCT/DE03/03213 includes an International Search Report, dated September 26, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is asserted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

Dated: May 6, 2005

By: Richard L. Mayer  
Richard L. Mayer  
Reg. No. 22,490

One Broadway  
New York, New York 10004  
Telephone: (212) 425-7200  
Facsimile: (212) 425-5288  
CUSTOMER NO. 26646

## DOSING DEVICE

~~Background of the Invention~~

**FIELD OF THE INVENTION**

The present invention proceeds from relates to a dosing device according to the species defined in the main claim.

5

**BACKGROUND INFORMATION**

In fuel-cell-assisted transport systems, so-called chemical reformers are used to recover the necessary hydrogen from hydrocarbon-containing fuels such as, for example, gasoline, ethanol, or methanol.

10

All the substances required by the reformer for execution of the reaction, for example air, water, and fuel, are conveyed to the reaction region ideally in a gaseous state. But because water and the fuels, for example methanol or gasoline, are preferably present in liquid form on board the transport system, they must first be heated shortly before they arrive at the reaction region of the reformer in order to evaporate them. This necessitates a pre-evaporator, a separate component, or a premixing chamber in the reformer, which are capable of making available the corresponding quantities of gaseous fuel and water vapor.

15

20

The temperature necessary for the chemical reaction in which, for example, the fuel is reformed into hydrogen (~~inter alia~~ *inter alia*) is made available by way of a so-called catalytic burner. Catalytic burners are components that have surfaces coated with a catalyst. In these catalytic burners, the fuel/air mixture is converted into heat and exhaust gases, the resulting heat being conveyed, for example, via the enveloping surfaces and/or via the hot exhaust gas stream, to the

25

30

corresponding components, such as the chemical reformer or an evaporator.

5 The conversion of fuel into heat is highly dependent on the size of the fuel droplets that strike the catalytic layer. The smaller the droplet size and the more uniformly the catalytic layer is wetted with the fuel droplets, the more completely the fuel is turned into heat and the higher the efficiency. The fuel is thus also converted more quickly, and pollutant  
10 emissions are reduced. Excessively large fuel droplets cause deposition on the catalytic layer and therefore slow conversion. That results, for example, in poor efficiency, especially during the cold-start phase.

15 Since the hydrogen is usually consumed immediately, chemical reformers must be capable of instantaneously adapting the production of hydrogen to demand, ~~e.g.~~ e.g., in the context of load changes or startup phases. Additional measures must be taken in the cold-start phase in particular, since the  
20 reformer is not supplying any waste heat. Conventional evaporators are not capable of instantaneously generating the corresponding quantities of gaseous reactants.

25 It is therefore useful to distribute the fuel through a dosing device in finely distributed form and/or with good placement onto locations and surfaces on which the fuels can properly evaporate, for example, into the reaction chamber or the premixing chamber of a reformer or catalytic burner, the internal surfaces of a cylindrical combustion chamber, or the  
30 internal enveloping surfaces of a catalytic burner. It is additionally useful to be able to select the geometry of the spray-discharged fuel in such a way that certain points or locations at which the fuel can evaporate poorly, or has a disadvantageous effect on the operating behavior of, for

example, a reformer, do not come directly into contact with the injected fuel.

Apparatuses for dosing fuels into reformers are known, for example, from U.S. Pat. No. 3,971,847. Here the fuel is fed in, by metering devices relatively remote from the reformer, through long metering conduits and a single nozzle into a temperature-controlled material stream. The fuel first strikes impact panels that are disposed after the outlet opening of the nozzle and are intended to cause turbulence in and distribution of the fuel, and then enters the reaction region of the reformer through a relatively long evaporation section that is necessary for the evaporation process. The long supply conduit allows the metering device to be insulated from thermal influences of the reformer.

A particular disadvantage of the apparatuses known from the aforementioned document is the fact that because of the simple design of the nozzle and the placement of the impact panels, there is only limited capability for controlled dosing of fuel into, for example, regions of the reformer having a high level of available heat. This results in a relatively large space requirement due to the need for a long and bulky evaporation section.

Problems additionally occur during cold starting, since long and bulky evaporation sections are slow to heat up and moreover dissipate a relatively large amount of unused heat. In particular, with nozzles and impact panels disposed as disclosed in U.S. Pat. No. 3,971,847 it is not possible to wet a hollow-cylindrical inner surface or spherical recess uniformly with fuel, or to exclude specific surfaces of the hollow cylinder from being wetted with fuel. The shape of the fuel cloud resulting from the metering operation can also be only insufficiently influenced.

## ~~Advantages of The Invention~~

### SUMMARY

The dosing device according to an exemplary embodiment of the  
5 ~~present invention having the characterizing features of the~~  
~~main claim has, in contrast,~~ has the advantage that because  
the nozzle body projects spherically into the metering  
chamber, and because the spray discharge openings are placed  
appropriately on the nozzle body projecting spherically into  
10 the metering chamber, the geometry of the spray-discharged  
fuel or the fuel cloud can be outstandingly well adapted to  
the circumstances prevailing in the metering chamber and the  
conditions arising therefrom. In particular, it is possible to  
wet hollow-cylindrical internal surfaces and spherical  
15 recesses uniformly with fuel.

It is additionally possible to shape the fuel cloud in such a  
way that a gap in the fuel cloud is formed. As a result of the  
exclusion of certain surfaces from being wetted with fuel, and  
20 gaps in the fuel cloud, it is possible, for example, to  
prevent any impingement of fuel on sensors mounted on the  
inner surface of the metering chamber, and to improve their  
accuracy.

25 ~~The features set forth in the dependent claims make possible~~  
~~advantageous refinements of the dosing device described in the~~  
~~main claim.~~

1: In ~~a refinement~~ an exemplary embodiment of the present  
30 invention, the nozzle body is shaped in hollow-cylindrical  
fashion at its end facing the metering conduit. This permits  
particularly simple and thus cost-saving manufacture, and  
moreover allows a thread to be applied in this region, so that  
the nozzle body can advantageously be connected to the

metering conduit in a particularly simple, sealed, and durable fashion.

The nozzle body ~~can advantageously~~ may also be welded, in particular laser-welded, to the supply conduit.

According to ~~a further refinement of the dosing device according to~~ an exemplary embodiment of the present invention, the spray discharge openings have different diameters. As a result, in particular, the fuel quantity passing through the respective spray discharge opening can be determined and can be adapted to the particular requirements.

In an exemplary embodiment of the present invention ~~It is additionally advantageous to place~~ the center axes of the spray discharge openings may be placed on a common intersection point, and ~~to place~~ the intersection point may be placed on the nozzle body axis. The geometry of the fuel cloud ~~can~~ may be adapted to particular requirements by selecting the location of the intersection point on the nozzle body axis.

Furthermore, the geometry of the fuel cloud or the spray-discharge geometry constituted by the emerging fuel streams ~~can also~~ may be adjusted and improved by asymmetrical positioning or by tilting the center axis of the spray discharge openings with respect to the nozzle body axis.

In an exemplary embodiment of the present invention, the ~~The~~ spray-discharge geometry of the fuel and the thermal conductivity characteristics of the nozzle body ~~can~~ may be positively influenced by reducing the wall thickness of the spherical portion of the nozzle body to a wall thickness which is less than that of the remaining portion of the nozzle body.

A fuel injection valve, such as the one used, for example,  
~~e.g.~~ for reciprocating-piston machines with internal  
combustion, ~~is advantageously utilized~~ may be used as the  
metering device. The use of such valves has several

5 advantages. For example, they permit particularly accurate  
open- or closed-loop control of fuel metering, in which  
context the metering can be controlled by way of several  
parameters such as pulse duty factor, clock frequency, and  
optionally stroke length. The dependency on pump pressure is  
10 much less pronounced than in the case of metering devices that  
control the volumetric flow of the fuel by way of the conduit  
cross section, and the dosing range is much larger.

In addition, fuel injection valves are economical, reliable  
15 components that have proven successful in many ways, are known  
in terms of their behavior, and are chemically stable with  
respect to the fuels used; this is true in particular of so-  
called low-pressure fuel injection valves that can be used  
with advantage here because of the thermal decoupling.

20 The metering conduit advantageously has a number of reduced-  
wall-thickness points that decrease the thermal conductivity  
of the metering conduit and can also serve as heat sinks.

25 The dosing device according to an exemplary embodiment of the  
present invention ~~preferably has~~ may have in the nozzle body a  
swirl insert having a swirl conduit for generating a swirl in  
the metered-in fuel or fuel/gas mixture. The mixture  
preparation and atomization of the fuel can thereby be further  
30 improved.

~~It is additionally advantageous if the~~ The shape of the swirl  
insert ~~is~~ may be identical to the internal geometry of the  
nozzle body, and ~~if~~ the swirl insert ~~is~~ may be disposed at a  
35 distance from the wall of the nozzle body. The velocity of the

fuel or the fuel/gas mixture at the swirl insert ~~can~~ may thereby be increased, and also easily adjusted. This may improve ~~improves~~ mixture preparation and atomization.

5 The swirl insert ~~preferably has~~ may have several swirl conduits, in which context the several swirl conduits ~~can~~ may extend parallel or can intersect as they extend. As a result, swirl generation ~~can~~ may easily be adapted to the properties of the fuel or the fuel/gas mixture, and the swirl intensity  
10 ~~can~~ may be adapted in accordance with requirements.

~~Lastly, it is advantageous to embody the~~ In an exemplary embodiment of the present invention the dosing device ~~with~~ may include an air inlet with which air or another gas can be  
15 introduced into the metering conduit. Mixture preparation ~~can~~ may thereby be further improved, and the fuel droplet size ~~can~~ may be further reduced. In addition, fuel or the fuel/gas mixture ~~can~~ may thus be eliminated or cleaned out of the metering conduit, in particular during shutdown phases, for  
20 example, by blowing it out with air through the air inlet. Uncontrolled emergence of fuel or a fuel/gas mixture out of the metering conduit is thus prevented.

The multi-part construction of the dosing device makes  
25 possible economical manufacture and the use of standardized components.

#### ~~Drawings~~

30 ~~Exemplary embodiments of the invention are depicted in simplified fashion in the drawings and explained in more detail in the description below. In the drawings:~~

~~Figure 1 schematically depicts an exemplary embodiment of a dosing device according to the present invention;~~  
35



~~Figure 2 is a schematic view of the nozzle body of Figure 1, from a point on the nozzle body axis located between the adapter piece and nozzle body;~~

~~Figure 3 schematically depicts the nozzle body depicted in Figure 2, in a side view of a section along line III-III;~~

~~Figure 4 schematically depicts a side view of a section of a further exemplary embodiment of a nozzle body according to the present invention;~~

~~Figure 5 schematically depicts a section of the exemplary embodiment with a hollow cylindrical metering chamber having a spherical recess;~~

~~Figure 6 schematically depicts a section of a further exemplary embodiment of a nozzle body according to the present invention having a swirl insert; and~~

~~Figure 7 schematically depicts a swirl insert.~~

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a schematically illustration of a dosing device according to an exemplary embodiment of the present invention.

Figure 2 is a front view of the nozzle body of Figure 1, from a point on the nozzle body axis located between the adapter piece and nozzle body.

Figure 3 is a side view of the nozzle body taken along section line III-III in Figure 2.

Figure 4 is a side view taken along section line III-III in Figure 2 of another exemplary embodiment of the nozzle body according to the present invention.

5 Figure 5 is a perspective view of the nozzle body in a hollow-cylindrical metering chamber having a spherical recess.

Figure 6 is a longitudinal section of a further exemplary embodiment of a nozzle body according to the present invention  
10 having a swirl insert.

Figure 7 is a longitudinal section of a further exemplary embodiment of a nozzle body according to the present invention  
15 having a swirl insert.

~~Description of The Exemplary Embodiment~~

**BRIEF DESCRIPTION OF THE DRAWINGS**

~~An exemplary embodiment of the invention is described below by way of example.~~

20 An exemplary embodiment of a dosing device 1 according to the present invention depicted in Figure 1 is embodied in the form of a dosing device 1 for the use of low-pressure fuel  
30 injection valves. Dosing device 1 ~~is suitable in particular~~ may be used for the input and atomization of fuel or a fuel/gas mixture into a metering chamber 10, shown by way of example in Figure 5, of a chemical reformer (not depicted in further detail) in order to recover hydrogen.

30 Dosing device 1 encompasses a metering device 2, which in this exemplary embodiment is embodied as a low-pressure fuel injection valve, an electrical connector 4, a fuel connector 3, an adapter piece 5 for receiving metering device 2, a tubular metering conduit 12, an air inlet 9, and a nozzle body  
35 7. Metering device 2 is tubular, fuel connector 3 being

located on the upper side. Metering of fuel into metering conduit 12 is accomplished on the lower of metering device 2, adapter piece 5 connecting metering device 2 and metering conduit 12 to one another in an externally hydraulically sealed manner. Tubular air inlet 9 opens into metering conduit 12 and is connected to it in sealing fashion via a threaded connection or welded connection, ~~in particular~~ such as a laser-welded connection.

The hollow-cylindrical end of nozzle body 7 facing toward metering conduit 12 encompasses the corresponding end of metering conduit 12 and is connected there in hydraulically sealed fashion to metering conduit 12 by way of a join that can be a welded or threaded connection, ~~in particular~~ such as a join produced by laser welding. Alternatively thereto, it is also possible for the corresponding end of metering conduit 12 to encompass the hollow-cylindrical end, facing toward it, of nozzle body 7. Metering conduit 12 itself is made, for example, of a standardized metal tube made of stainless steel.

Nozzle body 7 has, in its spherical portion 13 at the spray-discharge end that is shaped like a spherical segment or semi-sphere, several (in this exemplary embodiment, twenty) spray discharge openings 6 that are depicted in more detail in Figure 2 and Figure 3. In the exemplary embodiment depicted here, all the spray discharge openings 6 are disposed symmetrically with respect to a nozzle body axis 8 corresponding to longitudinal axis 15 of nozzle body 7, the imaginary extensions of center axes 14 of spray discharge openings 6 extending through an intersection point 11 located on nozzle body axis 8.

Fuel, for example gasoline, ethanol, or methanol, is conveyed to metering device 2 under pressure from a fuel pump and fuel line (not depicted) through fuel connector 3. When dosing

device 1 is in operation, the fuel flows downward and is metered, through the sealing fit (not depicted) located in the lower end of metering device 2, into metering conduit 12 in known fashion by opening and closing the sealing fit. Air or  
5 other gases, for example combustible residual gases from a reforming or fuel-cell process, can be conveyed, for mixture preparation, through air inlet 9 that opens laterally into metering conduit 12 near metering device 2. As it continues, the fuel is transported through metering conduit 12 to nozzle  
10 body 7 and is there metered through spray discharge openings 6 into metering chamber 10 depicted, by way of example, in Figure 5.

Figure 2 shows the nozzle body 7 depicted in Figure 1, in  
15 enlarged fashion, from a point on nozzle body axis 8 located in metering chamber 10. In this view, injection openings 6 lie on two lines at right angles to one another that intersect at nozzle body axis 8, depicted here as a dot.

20 Figure 3 is a side view of a section along line III-III through nozzle body 7 depicted in Figure 2. It is clearly evident that in this exemplary embodiment, center axes 14 of spray discharge openings 6 intersect the common intersection point 11 located on nozzle body axis 8. In this exemplary  
25 embodiment, twenty spray discharge openings 6 are located, disposed symmetrically with respect to nozzle body axis 8, in spherically shaped portion 13 of nozzle body 7 that projects into metering chamber 10 depicted, by way of example, in Figure 4.

30 Figure 4 is a side view of a further exemplary embodiment of nozzle body 7 depicted in Figure 2, similar to the exemplary embodiment depicted in Figure 3. The wall thickness of spherical portion 13 of nozzle body 7 is, however, thinner as  
35 compared with the remaining wall thickness of nozzle body 7.

Figure 5 shows nozzle body 7 mounted on supply conduit 12 and projecting into metering chamber 10. Metering chamber 10 is cylindrical, the end of metering chamber 10 that is depicted having a spherical recess. Fuel is metered through spray discharge openings 6 (not depicted in Figure 4) into this region. ~~It is advantageous in this context that as~~ As a result of the spherical conformation of nozzle body 7 at the spray-discharge end, spray discharge openings 6 are disposed in such a way that the spherical recess of metering chamber 10 is uniformly impinged upon by fuel.

Figure 6 is a schematic sectioned depiction of a further exemplary embodiment of a nozzle body 7 according to the present invention having a swirl insert 16 disposed in the interior of nozzle body 7. The wall of nozzle body 7 is shown merely schematically as a line, without spray discharge openings 6 that are present. Swirl insert 16 has peripherally extending swirl conduits 17 that are inclined with respect to a longitudinal swirl insert axis 18 and, thus, impart a rotation to the fuel or fuel/gas mixture flowing past. In this exemplary embodiment, longitudinal swirl insert axis 18 is coincident with center axis 15 of nozzle body 7.

The shape of swirl insert 16 is adapted both radially and, toward spherical portion 13 of nozzle body 7, to the internal shape of nozzle body 7. In this exemplary embodiment, swirl insert 16 is spaced away at a uniform distance 19, which here is, for example, ~~e.g.~~ less than 0.2 mm, from nozzle body 7 at the radial sides and at its spherical portion. The relatively small distance 19 results in a pressure increase in swirl conduits 17 and, thus, in better preparation.

Figure 7 schematically depicts a further swirl insert 16 in which swirl conduits 17 do not extend in parallel fashion as

in the exemplary embodiment of Figure 6, but instead cross as they extend peripherally.